

PRODUCT DATA SHEET

STRONG GRIP - Solvent Free

A HIGH STRENGTH SOLVENT FREE GAP FILLING MULTI USE ADHESIVE

PRODUCT DESCRIPTION

STRONG GRIP - Solvent Free is a high strength solvent free gap filling multi use adhesive that provides a quick grab and replaces mechanical fixings in many home improvement applications.

USES

- Sticking wood, metal, PVC, most plastics, glass, aluminium, concrete, render, stone, paper, cork, ceramics plaster/plasterboard, rockwool, Puf foam board, Styrofoam, breezeblock etc
- Bonding dado rails, architraves and skirting
- Fixing wall cladding direct to internal wall surfaces or timber battens.
- Fixing battens directly onto walls without fastenings.
- Bonding carpet gripper systems to most floors without the need for nails or tacks.
- Bonding stair nosing to concrete or wooden stairs.
- Securing aluminium or other skin panels to the framework or portable industrial buildings and caravans.

CHARACTERISTICS / ADVANTAGES

- Solvent free - environmentally friendly formulation
- Excellent adhesion/bond strength - adheres to most common surfaces -QUICKLY
- Good early grab properties - usable in both vertical and horizontal positions.
- Dries white
- Will adhere to damp surfaces.
- Water clean up - no hazardous solvents.
- Overpaintable.

PRODUCT INFORMATION

Packaging	290ml Cartridge
Colour	White
Shelf Life	24 months from date of manufacture
Storage Conditions	Store in cool dry conditions between + 5°C and 25°C
Density	1.49 g/cm ³
Solid content by weight	75-80%
Consistency	White thixotropic paste (ready to use)

APPLICATION INFORMATION

Yield	ca. 10.5 linear metres (6mm bead)
Ambient Air Temperature	+4°C to +35°C
Curing Rate	Initial: 30 mins. Final: 24-48 hours (dep on substrate)
Open Time	Max 10 mins at 23°C and 50% R.H

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Wood, plaster and brick may be damp but not running wet (NOTE This will slow down the drying time). Use mechanical abrasion to clean porous surfaces if necessary before application.

APPLICATION METHOD / TOOLS

- Surfaces must be, clean, dry and free from dust, grease, loose material etc. At least one surface must be porous.
- Prime dusty surfaces with EVERBUILD PVA BOND diluted 1:4 with water and allow to dry.
- Apply using a standard sealant gun, cut tip of cartridge, apply nozzle and cut an opening to suite the required bead size.
- For bonding heavy items (Plasterboard/worktops/wall panels etc) apply adhesive all the way around the edge of the item (30-50mm from edge) and cover back with beads of adhesive at 300mm intervals. Alternatively, apply adhesive direct to battons and press into place. NOTE.
- With heavy items, always provide temporary support until the adhesive dries.
- For bonding lightweight items (covings, dado rails, skirting etc) apply adhesive to back of item in one or two continuous beads and press immediately into place.
- Where gap filling is required, mark the areas where there is a large gap and apply a thicker bead to these areas.
- In all cases, clean up excess adhesive immediately with a damp cloth.

LIMITATIONS

- At least one surface must be porous.
- In damp, cold or humid conditions, curing time may be significantly extended.
- Do not use in permanently damp/wet conditions.
- Do not use in situations where both surfaces are non-porous (e.g. plastic/plastic or metal/metal) - use GUN A NAIL EXTRA.
- Do not use as a mirror adhesive: use EVERBUILD MIRROR MATE

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



1st Floor
19 Clifftown Road
Southend-On-Sea
SS1 1AB

Tel 0844 887 1401

www.strongfastglobal.com

Pinnacle House,
Newtown Cross,
The Ward,
Co. Dublin,
D11 K27C

Tel 0800 970 2414